


ACQUEX LED-M





5 YEARS
warranty

Explosionproof IP66 & IK08 LED LUMINAIRE

Zone 2 and 22
GAS & DUST

Good payback time
VERSUS CONVENTIONAL SOLUTIONS

100% instant light
NO START UP-TIME

50,000h
LONG SERVICE LIFE

Emergency version
AVAILABLE

94/9 EC
ATEX DIRECTIVE



5 YEARS warranty



MATERIAL

- Housing Glass fibre reinforced polyester in yellow (RAL 1003)
- Diffuser Transparent polycarbonate
- Gear tray White laquered steel plate
- Clips Stainless Steel
- Gasket Polyurethane, poured in one piece
- One wire entry of \varnothing 20.5mm

LED-SYSTEM & CONTROL GEAR



- LED module BAG
- Mid-power LEDs
- 4,000°K neutral white
- Ra>80
- 50.000h service life [L80]
- Electronic control gear BAG

MOUNTING ACCESSORIES

Stainless steel fixing springs included.



ACCESSORIES

(Must be ordered separately.)

- Polyamide ATEX cable gland M20x1.5 IP68 for cable range \varnothing 6-13 (10115833)
- Brass nickel plated ATEX cable gland M20x1.5 IP68 for cable range \varnothing 6-13 (10115832)



PRODUCT OPTIONS



850°C IK08 IP66
 Rated voltage 220-240V Frequency 0-50/60Hz +40°C -20°C SELV

ACQUEX LED-M

Zone 2, 22.

Explosion protection is a delicate and complex issue. Human lives may depend on it. Zalux offers you reliable explosion protected lighting equipped with state of the art LED technology. Designed to be used in hazardous areas where an explosive atmosphere persists for a short period as standard illumination or as emergency illumination.

Suitable for lighting premises of oil and gas, pharmaceutical, chemical, food and other industrial sites


TECHNICAL FEATURES - LUMINAIRE

Description	Power	Efficiency	Luminous flux
ACQUEX LED-M 1x0.6 PC	22W	100 lm/W	2,200 lm
ACQUEX LED-M 1x1.2 PC	40W	110 lm/W	4,400 lm
ACQUEX LED-M 1x1.5 PC	45W	116 lm/W	5,200 lm

TECHNICAL FEATURES - EMERGENCY VERSION 3h (NiCd battery)

Description	Luminous flux		Power	
	Emergency operation	Normal operation	Current charging (I max first 24 hours)	Average wattage after the first 24h of charging
ACQUEX LED-M 1x1.2 EB3H PC	340 lm	4,400 lm	200 mA	40W
ACQUEX LED-M 1x1.5 EB3h PC	330 lm	5,200 lm	200 mA	45W

Description	Order number	Order number - Emergency -	Units/Box	L x W x H (mm)	Box	EuroPallet Groupage	EuroPallet Full truck
ACQUEX LED-M 1x0.6 PC	10121627	-	1	675x151x105	2.00	150	90+90
ACQUEX LED-M 1x1.2 PC	10121628	10121630	1	1289x151x105	3.25	75	45+45
ACQUEX LED-M 1x1.5 PC	10121629	10121631	1	1589x151x105	3.60	75	45+45



ACQUEX LED-M 1x1.2

II 3 G Ex nA IIC T6 Gc

II 3 D Ex t IIIC T85°C Dc IP66

ATEX Directive 94/9 EC