


LEXIT




IP65

Code **LX32N30ABR**

Short code **LX1202**



A=309mm B=283mm C=41mm
D=99mm E=185mm F=290mm G=8mm



Signaling visibility: 32 meters

Luminaire description

- LEXIT 3H MAINTAINED IP65 32M REST MODE

Technical characteristics

- Battery status: Battery connected green LED on; battery disconnected red LED on
- Function: Rest Mode (Self-contained with rest mode)
- Duration: 3h
- Type: M (Maintained)
- Battery: Ni-Cd 4,8V 0,5Ah
- Battery type: Nickel Cadmium
- Recharge time: 12h
- Power supply: 230Vac 50-60Hz
- Insulation class: II
- IP protection degree: IP65
- Working temperature: 0°C to +40°C
- Colour: Grey
- Signaling visibility (EN 1838): 32 meters
- Compliant to European standards: EN 60598-1, EN 60598-2-22, EN 1838, EN 7010
- Photobiological safety exempt group according to EN 62471
- Compliant to RoHS 2011/65/UE
- Glow wire 850 °C
- Kit of pictograms included
- Installation: ceiling, flag-style, wall*, suspended*, false-ceiling recessed*, wall over 503 box* (* with accessory)
- 5 year warranty (please read the Warranty terms)

Lamp characteristics

- Type: LED
- Lamps: 8 LED
- Colour temperature: 6000K



An UNI EN ISO 9001 certified company

LINERGY Srl - Via A. De Gasperi, 9 - 63075 Acquaviva Picena (AP) - ITALY - Tel. +39 0735 5974 - Fax +39 0735 597474 - www.linergy.it - info@linergy.it

Subject to change without notice. 10/17-1